HKS NEW RELEASE INFORMATION

ELECTRONIC VALVE CONTROLLER



(Features)

- EVC6's LCD full color monitor is upgraded for better visibility with a larger sized monitor. The monitor size is enlarged to 2.4inch from 2.2 inch. (The case remains in the same size.)
- Basic performance as a boost controller is the same as EVC6-IR. Correction map grid point: 10×10.
 Pressure correction range: -180~180.
 More precise correction is possible for modern smaller sized turbo.
- Monitor Navigation System easily leads the user to the correct setting and logging screens.
- The proven Stepping Motor is utilized as a valve unit.



FUNCTION



Indicates the current boost mode.

Blinks and buzzes while the

Indicates one of the following: Intake Manifold Pressure, Speed, Engine RPM, and Throttle

Blinks and buzzes with the bar graph when a certain



Displays the warning value or peak hold value.

Displays the speed or engine RPM.

Displays the throttle opening angle.


Displays the current boost value.

Easy and securely setup are possible by

EVC6-IR 2.4 LCD Display Size



【LCD Display Comparison】 Upper:EVC6-IR 2.4 (New) Lower:EVC6-IR (Old)



EVC6-IR 2.4

Product	Code No.	Price
EVC6-IR 2.4	45003-AK012	

