June. 2015

NEW RELEASE INFORMATION CAPACITY UP GRADE KIT for 212 3.41

Capacity Upgrade Kit for the 2JZ-GTE engine which got so much attention from all over the world is available again in a limited quantity! This kit was developed with drag racing in mind. HKS 2JZ-GTE 3.41 Kit makes approximately 1000ps power levels possible. High quality "MADE IN JAPAN" lives up to our customers' demands.

This kit is recommended to those who want to tune to the highest levels including engine internals.

*In-house test result. Maximum engine RPM – Approx. 7500rprReproduce!! Limited in Quantity!!

FEATURES

POINT I PISTON KIT

- Carefully selected specially forged raw materials used.
- HKS original Ni plated and molybdenum coated pistons are included.
- Ni plating treatment was done on the top side and top land groove which enhances durability against knock, high combustion pressure and protects top land groove from deforming.
- Ti coated top ring improves its frictional properties and scuffing resistance characteristic.

POINT^② CONNECTING ROD

- Highly strength H-beam design. The engine capacity is increased by increased stroke and torque at low -mid speed range is improved.
- Compatible with standard stroke

POINT③ CRANKSHAFT STROKE 94.0mm

- HKS special forged material made high strength crankshaft.
- · Long stroke and lightweight counterweighted crankshaft was designed to improve the engine response.


POINT ADDITIONAL MODIFICATION

- 1mm over sized pistons requires cylinder bore and honing.
- Recess modification inside the engine block is not required.
- * Recess modification may be required depending on the cylinder block's individual difference.

TEST VEHICLE DA	TA					
Bore / Stroke	φ87×94mm					
Displacement	3352.8CC					
Comp. Ratio	8.6					
PRODUCT						
Head Gasket	t=1.6mm (φ88)					
Piston	φ87 Prototype					
Crankshaft	St=94mm Prototype					
Con'rod	HKS H-beam					
Camshaft	IN:272° EX:272° (Both Valve Timing:110°)					
Spark Plug	#11 equivalent					
Turbine	T51R SPL					
Wastegate	GT II Wastegate					
Surge Tank	HKS SPL					
Throttle	Infinity Q45					
Exhaust Manifold	HKS SPL					
ECT	F-CON VPRO					
A/F	Approx. 12					
Fuel	DRAG GAS					
Engine Oil	Pro Oil					
Intercooler	HKS SPL					
Metal Bearing	Stock #4 (Center) Upper metal only for journal.					

			Stock	HKS 3.4L
	Bore di	a.mm	86	87
Piston	Displace	ement cc	2997.3	3352.8
	Comp. Ratio	G/K 1.2 mm	8.50	8.80
		G/K 1.6 mm		8.60
		G/K 2.0 mm		8.30
	Boring/	Horning	-	Required
	Valve R	ecess	VVT-i	HKS Cam/VVT-I Valcon
Con'rod	Big end	dia.	55φ	55φ
	Bolt siz	е	764.2g	598g
	Remark	s	Forged I-beam	Billet H-beam
Crankshaft	Stroke	mm	86.00	94.00
	Main journal dia.		62	62
	Materia		Vanadium Steel	SCM
	Remark	s	Forged Full- counter	Forged Billet Full- counter

PERFORMANCE



[2JZ 3.4L KIT]

Product	Engine	Capacity	Туре	Boring/Horning Modification	Full Flow Modification	Code No.	Price	Remarks
ΤΟΥΟΤΑ								
			Not Required	Not Required	21004-AT001		Ni Forged Piston Kit +H-beam	
21Z 3.4L KIT		3352.8cc φ87.0-22					Con'rod + Billet Crankshaft	
2JZ 3.4L KI1 2JZ-GTE	3332.000 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Not Required	Not Required	21004-A1001		※Allowable Engine RPM:		
								7500rpm/min or less



HKS Co., Ltd.