



# NEW RELEASE INFORMATION



Basic model of S-STYLE range that has simple structure for beautiful style and a comfortable ride.



**for RU1 VEZEL**

- Mono Tube
- Fixed Dampening
- Shock-body Length Adjustable
- PNE Coat
- Special Oil
- Spring Rate Change Available
- Inverted Strut Type
- Overhaul Available
- 1 Year Warranty

### ■ FEATURES

- Firmness on the rear side was eliminated whilst maintaining the factory nimble driving feeling. A comfortable ride is provided for both front and rear seat passengers.
- Even though the spring rate is low, carefully selected internal parts support cornering performance, stable driving at high speed, and supple and persistent driving characteristics.

### ■ PARTS LIST & DAMPER STRUCTURE

Parts List		
	Front Damper Assy	2
	Rear Damper Assy	2
	Rear Spring	2
	Rear Ride Height Adjuster Assy	2
	Rubber Seat	2
	Spanner Wrench (Large)	2
	Tie Wrap	8
	Warranty Certificate	1
	Installation Guide	1

  

Damper Components	
<b>FRONT</b>	<b>REAR</b>
<p>FACTORY Torque Spec: 90N·m</p> <p>NUT Torque Spec: 34N·m</p> <p>PLATE UPPER MOUNT ASSY SPHERICAL COLLAR</p> <p>PLATE (YELLOW) Make sure the plate's orientation is correct. The taper of a hole must be faced downward (to the ball's seat).</p> <p>DUST BOOT</p> <p>SPRING</p> <p>LOCKING SPRING Torque Spec: 50N·m</p> <p>LOCKING BRACKET Torque Spec: 100N·m</p> <p>BRACKET</p>	<p>NUT (FACTORY) Torque Spec: 21N·m</p> <p>WASHER (FACTORY)</p> <p>DAMPER MOUNTING WASHER (FACTORY) Make sure to install in the same direction of a factory part.</p> <p>DAMPER MOUNTING RUBBER (FACTORY)</p> <p>DAMPER MOUNTING SEAT RUBBER (FACTORY)</p> <p>DUST COVER (FACTORY)</p> <p>DAMPER MOUNTING (FACTORY)</p> <p>HUMP RUBBER (FACTORY)</p> <p>LOCKING BRACKET Torque Spec: 50N·m</p> <p>RUBBER SEAT</p> <p>REAR RIDE HEIGHT ADJUSTER ASSY</p> <p>LOCKING SPRING Torque Spec: 60N·m</p> <p>RIDE HEIGHT ADJUSTER</p> <p>REAR SPRING</p> <p>LOWER MOUNTING RUBBER (FACTORY)</p>

VEHICLE	MODEL	ENGINE	YEAR	SPRING RATE	FREE LENGTH	VEHICLE'S HEIGHT	CODE NO.	PRICE
VEZEL	RU1	L15B	13/12~	F=29(3) R=28(29)	300(Barrel) /Special	F=-15(0 - -49) R=-27(0 - -68)	80110-AH122	

UPPER MOUNT	UPPER MOUNT CHANGE	SPRING RATE CHANGE	REMARKS
F=Stock R=Stock	N/A	F=Available R=N/A	The setting at shipment is based on Hybrid vehicle. To install this product to gasoline vehicles, adjust the setting referring to the data for testing before installation.

