

MAX IV GT

for **BM2FS/BM5FS AXELA**

Next generation suspension with high controllability for sporty driving and improved ride quality for street driving.



- | | | | | |
|------------------|---------------------------|------------------------------|--------------------|-----------------|
| Mono Tube | 30-way Adjustable Damping | Shock-body Length Adjustable | Special Oil | PNE Coating |
| Aluminum Bracket | Rubber Upper Mount | Spec. Change Available | Overhaul Available | 1 year Warranty |

■ Features

- This product maintains a sufficient stroke control not only by spring rate but also damping force to improve ride comfort and stability that can be experienced on rough or bumpy roads.
- The direct coiling springs are selected for the front and rear to improve the flexibility of setup.

■ Kit Parts

Parts List			Suspension Components				
	Front Suspension Assy	2					
	Rear Shock Absorber Assy	2					
	Rear Spring	2					
	Rear Ride Height Adjuster Assy	2					
	Dial	2					1
	Cable	2					8
	Screw	6					1
	Allen Wrench	1					1
	Spanner Wrench (Slotted)	1					

VEHICLE	MODEL	ENGINE	YEAR	SPRING RATE [N/mm (kgf/mm)]	FREE LENGTH	VEHICLE'S HEIGHT Default(High-Low)	CODE NO.	PRICE
AXELA	BM2FS	SH-VPTR	14/1~16/6	F=39(4) R=29(3)	250(Barrel)/ 250(Barrel)	F=-29(0 - -85) R=-32(-10 - -83)	80230-AZ005	
	BM5FS	P5-VPS	13/11~16/6			F=2(0 - -59) R=-31(-9 - -82)		

UPPER MOUNT	UPPER MOUNT CHANGE BEFORE SHIPMENT	SPRING RATE CHANGE BEFORE SHIPMENT	REMARKS
F=Rubber R=Rubber	N/A	F=Available R=Available	Recommended vehicle height for BM5FS is F=-24/R=-42. ※Malfunction of a radar, camera, sensor, etc. may occur due to the vehicle's height change. HKS won't be responsible for any malfunction after installing this product.